




BEARING FORGE OF AMERICA CORP.



6211 6211zz 6211 2RS Distributor SKF NSK
NTN NACHI High Quality Good Price Deep
Groove Ball Bearings

Bearing No. 6211

| | |
|-------------------------------|--------------------------|
| Size | 55x100x21 mm |
| Bore Diameter | 55 mm |
| Outer Diameter | 100 mm |
| Width | 21 mm |
| d | 55 mm |
| D | 100 mm |
| B | 21 mm |
| C | 21 mm |
| r min. | 1.5 mm |
| da min. | 64 mm |
| Da max. | 91 mm |
| ra max. | 1.5 mm |
| Weight | 0.607 Kg |
| Basic dynamic load rating (C) | 43,5 kN |
| Basic static load rating (C0) | 29,3 kN |
| (Grease) Lubrication Speed | 6300 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NACHI |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| EAN | 4991893724493 |
| Product Group | B00308 |
| Enclosure | Open |

6211 Bearing 2D drawings and 3D CAD models



BEARING FORGE OF AMERICA CORP.

| | |
|---------------------------------|--|
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 55MM Bore; 100MM Outside Diameter; 21MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage |
| Other Features | Deep Groove |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nachiamerica.com |
| Outer Race Width | 0.827 Inch 21 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outside Diameter | 3.937 Inch 100 Millimeter |
| Bore | 2.165 Inch 55 Millimeter |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Bore Size | 55 mm |
| Width | 21 mm |
| Fillet Radius/Chamfer | 1.5 mm |
| | |



BEARING FORGE OF AMERICA CORP.

| | |
|-------------------------|-------------------|
| Dynamic Load Rating | 43,500 N |
| Static Load Rating | 29,300 N |
| Limiting Speed - Grease | 6,400 rpm |
| Limiting Speed - Oil | 7,700 rpm |
| Factor f_0 | 14.4 |
| Radial Clearance | 0.008 to 0.028 mm |
| d_a (min) | 64 mm |
| D_a (max) | 91 mm |
| r_a (max) | 1.5 mm |